

	ORBIT	SKYE	LUNA	LUNAPRO
Recessed Downlights	An entry level, 360° rotation, 80° tilt downlight. <b>Aperture:</b> 2", 4" <b>Del. Lumens:</b> 365-860	Magnetic trims, below ceiling CCT, round and square. <b>Aperture:</b> 4", 6" <b>Del. Lumens:</b> 760-1855	Our flagship downlight. Can be used almost anywhere. <b>Aperture Size:</b> 2", 3", 3.5", 4" <b>Del. Lumens:</b> 604-818	Fixed, wall wash, trimless, round and square. <b>Aperture:</b> 3.5", 5", 6" <b>Del. Lumens:</b> 705-2420
Multiples			2 or 3-light multiples. <b>Aperture:</b> 3.5" <b>Del. Lumens:</b> 1060-4752	
Cylinders				

	FORUM <sup>®</sup> Essential	SHADE MINI	FORUM <sup>®</sup> Panel	FORUM <sup>®</sup> Frame
T-Bar and Surface Mount	Economical troffer solution with consistent illumination. <b>Del. Lumens:</b> 2840-6680	Mount onto octagon box or SlimLED, round and square. <b>Aperture:</b> 4", 6" <b>Del. Lumens:</b> 520-1120	Best-in-class premium panel, modern alternative to troffers. <b>Del. Lumens:</b> 2100-6930	Modular frame system for FORUM panels.

	Liteline Track	POWERGEAR <sup>®</sup>	Sora / Delta / Apollo	Flight / Teardrop / Focus
Track	Single-circuit for residential and light commercial use. <b>Dims:</b> 1" x 3/4"	A rigid 2-circuit, 2-neutral, or 3-circuit track system. <b>Dims:</b> 1-3/8" x 1-3/8"	Classic style, full rotation and 90-degree tilt track fixtures. <b>Diameter:</b> 2.5", 3" <b>Del. Lumens:</b> 611-1050	Offers diverse output and 90-degree compatibility. <b>Diameter:</b> 2", 3" <b>Del. Lumens:</b> 640-3180

	STRIPE <sup>®</sup> NEW	FORUM <sup>®</sup> Linear		
Linear	Plug and play, 120V linear system with integrated driver. <b>Dims:</b> 1-4/5" x 1-2/5" <b>Del. Lumens:</b> 700-1800	Bridges gap between surface, troffer and recessed lighting. <b>Del. Lumens:</b> 1650-4750		

	Steplights	LEDBar	SLIMLED PUCK	MOON PUCK
Millwork, Steplights, Undercabinet	For indoor or outdoor settings, ideal for hallways, walkways. <b>Del. Lumens:</b> Up to 62	Line voltage linear light, link up to 10 fixtures. <b>Dims:</b> 1" x 1-5/16" <b>Del. Lumens:</b> 350-1800	Low profile millwork light, suitable for high vibration areas. <b>Aperture:</b> 2" <b>Del. Lumens:</b> Up to 145	Smooth wall wash for undercabinet or wayfinding. <b>Aperture:</b> 2" <b>Del. Lumens:</b> Up to 210

	DINE <sup>®</sup> NEW	SIGMA	SIGMA <sup>®</sup> COMMERCIAL	GENESIS	HELIOS	SIRIUS <sup>®</sup> NEW
	Highly configurable with ability to stack up to 1/4" of media. <b>Aperture Size:</b> 3" <b>Del. Lumens:</b> 600-1200	Wide range of optics, trim styles, finishes and accessories. <b>Aperture:</b> 1.5", 2" <b>Del. Lumens:</b> 700-1600	Building upon SIGMA 2, offering higher outputs. <b>Aperture:</b> 4", 5", 6", 7", 9" <b>Del. Lumens:</b> 1000-4500	Ultra high output commercial fixture. <b>Aperture:</b> 4", 6", 8", 10" <b>Del. Lumens:</b> 1000-9000	Ultimate control of optical performance. <b>Aperture:</b> 2", 3" <b>Del. Lumens:</b> 1800	
		2 or 3-light multiples. <b>Aperture:</b> 3.5" <b>Del. Lumens:</b> 1280-1920	2 or 3-light adjustable pulldown fixtures. <b>Aperture:</b> 3.5" <b>Del. Lumens:</b> Up to 2500			A 5-cell recessed downlight, multiple trim and baffle colors. <b>Dims:</b> 7" x 1" <b>Del. Lumens:</b> Up to 580

	DINE	APF	FLEX	GENESIS		
	A warm, precise circle of light for hospitality applications. <b>Diameter:</b> 2" <b>Del. Lumens:</b> 600-900	Sleek, surface mount cylinder or pendant. <b>Diameter:</b> 3" <b>Del. Lumens:</b> 1200-2300	7 mounting options on 1 body including pendant and track. <b>Diameter:</b> 2", 3" <b>Del. Lumens:</b> 900-4140	Ultra high output commercial cylinder with variety of controls. <b>Diameter:</b> 4", 6" <b>Del. Lumens:</b> 1000-8000		

	EDGE <sup>™</sup>	SHADE				
	For T-bar, doesn't interfere with above ceiling mechanical. <b>Del. Lumens:</b> 2100-5700	Combines best-in-class panel with decorative frame element. <b>Del. Lumens:</b> 2100-6930				

	DINE	A-Line / A-Beam	FLEX	ATLAS	CLICK <sup>™</sup>	
	A warm, precise circle of light for hospitality applications. <b>Diameter:</b> 2" <b>Del. Lumens:</b> 600-900	Rigid 1-channel track with fewer suspension points. <b>Dims:</b> 1-3/8" x 5/8"	7 mounting options on 1 body including pendant and track. <b>Diameter:</b> 2", 3" <b>Del. Lumens:</b> 900-4140	Commercial grade with universal voltage 120-277V. <b>Diameter:</b> 2", 3" <b>Del. Lumens:</b> 1200-3200	Modular and linear track, extends wall to ceiling. <b>Dims:</b> 1" x 2-5/8" <b>Del. Lumens:</b> 570-1500	

	PEGA					
			Thin profile linear, that can be ordered as complete assembly. <b>Dims:</b> 15/16" x 1" <b>Del. Lumens:</b> Up to 500lm/ft			

	MicroPot <sup>™</sup>	MicroLED <sup>™</sup>	VELA	FOSSIL		
	Small fixture suitable for insulated applications. <b>Aperture:</b> 2-3/16" <b>Del. Lumens:</b> Up to 235	Ultra small accent light, providing directional lighting. <b>Aperture:</b> 1-5/16" <b>Del. Lumens:</b> Up to 102	Recessed, thin profile, can be ordered as complete assembly. <b>Dims:</b> 1-1/16" x 1/2" <b>Del. Lumens:</b> Up to 500lm/ft	Pre-formed plaster trimless step light, blends into wall. <b>Del. Lumens:</b> Up to 70		



IC

DLC



JA8

CP



CCT3

CCT5



Declare.



US

LISTED

\*Selectable wattage is not available on Forum Panel and Shade 6" x 2", 1' x 1', 1' x 2' models.  
\*\*EDGE 1' x 1' model only available in fixed 20W and 1' x 2' only available in fixed 30W.