LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2020, All rights reserved.

S247XX-E30ZC-TX-XX

Photometric Testing Report

Light efficiency:

67 Lumen/Watt


Color temperature:

3098 K

Light quality:


CRI:93.3, R_g:103.1, R_f:91.3
P: 2 / V: - / F: 2

Output:	**1375 lm**
Peak:	**1543 cd**
Power:	**20.5 W**
Voltage:	**119 V**
Current:	**0.173 A**
PF:	**0.99**
THD:	**6.07 %**




Angular Distribution

0° and 90° plane




Product name:
S247XX-E30ZC-TX-XX

Test Date:
8/20/2026




Polar Diagram




BUG Diagram

ISO Candela Diagram



ISO Lux Diagram



Mounting height: 3.05 meters (10 feet)

Lux at center:	52 lx
3%	1.56 lx
5%	2.60 lx
10%	5.20 lx
30%	15.60 lx
50%	26.00 lx

Conditions:
Number of planes: 16
Lux distribution on a surface when lamp is mounted at 3.05 meters from the surface.

LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736


Copyright © 2020, All rights reserved.

S247XX-E30ZC-TX-XX


Liteline


Photometric Testing Report


ANSI/IES TM-30-18 P: **2** / V: **-** / F: **2**




Hue Bin	R_f	Shifts (%) Chroma	Hue
1	93	-3%	-2%
2	94	-3%	2%
3	88	0%	6%
4	89	3%	6%
5	92	5%	4%
6	90	6%	0%
7	89	4%	-6%
8	93	1%	-4%
9	94	-2%	-3%
10	93	-4%	1%
11	88	-1%	7%
12	91	4%	4%
13	93	5%	0%
14	91	6%	-4%
15	90	3%	-6%
16	89	1%	-9%









Red: 39%, Power=15.1mW

Blue: 6.7%, Power=4.7mW

Green: 24.8%, Power=17.2mW

UVA: 0%, Power=0.0mW

Dominant Wavelength:583nm

1st Peak Wavelength: 627nm

2nd Peak Wavelength:448nm

