LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2020, All rights reserved.

S250XX-MDWZC-TX-XX

Photometric Testing Report

Light efficiency:
57 Lumen/Watt


Color temperature:
3120 K

Light quality:
CRI:93.5, R_g:102.4, R_f:91.4
P: 2 / V: - / F: 2

Output:	**1044 lm**
Peak:	999 cd
Power:	18.5 W
Voltage:	119 V
Current:	0.157 A
PF:	0.99
THD:	12 %


Angular Distribution

0° and 90° plane




Product name:
S250XX-MDWZC-TX-XX

Test Date:
8/27/2026




Polar Diagram




BUG Diagram

ISO Candela Diagram



ISO Lux Diagram



Mounting height: 3.05 meters (10 feet)

Lux at center:	46 lx
3%	1.38 lx
5%	2.30 lx
10%	4.60 lx
30%	13.80 lx
50%	23.00 lx

Conditions:
Number of planes: 16
Lux distribution on a surface when lamp is mounted at 3.05 meters from the surface.

LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736


Copyright © 2020, All rights reserved.

S250XX-MDWZC-TX-XX


Liteline


Photometric Testing Report


ANSI/IES TM-30-18 P: **2** / V: **-** / F: **2**




Hue Bin	R_f	Shifts (%) Chroma	Hue
1	94	-3%	-1%
2	94	-3%	2%
3	89	0%	6%
4	92	1%	5%
5	92	2%	4%
6	92	5%	0%
7	93	1%	-4%
8	95	0%	-3%
9	95	-2%	0%
10	89	-3%	6%
11	85	0%	10%
12	89	5%	5%
13	93	5%	0%
14	90	7%	-4%
15	91	2%	-5%
16	88	2%	-10%









Red: 39.5%, Power=11.9mW

Blue: 8.1%, Power=5.3mW

Green: 24.3%, Power=13.4mW

UVA: 0%, Power=0.0mW

Dominant Wavelength:584nm

1st Peak Wavelength: 627nm

2nd Peak Wavelength:452nm

