LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2023, All rights reserved.


Photometric Testing Report

Light efficiency:
53 Lumen/Watt

Color temperature:
3163 K


Light quality:
CRI:94.6, R_g:99.2, R_f:92.8
R9: 65.1 / P: 2 / V: - / F: 2

Output:	**1259 lm**
Peak:	**1576 cd**
Power:	**23.7 W**
Voltage:	**120 V**
Current:	**0.198 A**
PF:	**0.99**
THD:	**7.65 %**



Angular Distribution

0° and 90° plane



Product name:
S251XX-ETWWC-TX-XX

Test Date:
8/31/2026


Beam Angle (50% of the brightness of the centre):
53.3°

Field Angle (10% of the brightness of the centre):
79.3°

Cut Off Angle (2.5% of the brightness of the centre):
95.7°

Beam Details

*measured at centre of beam



LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2023, All rights reserved.


S251XX-ETWWC-TX-XX

Photometric Testing Report

Zonal Lumen Summary

Zone	Lumen	%Luminaire
0-30	944	74.98%
0-40	1174	93.25%
0-60	1247	99.05%
60-90	12.5	0.99%
70-100	2.17	0.17%
90-120	0.002	0.00%
0-90	1259	100.00%
90-180	0.002	0.00%
0-180	1259	100.00%

ISO Lux Diagram



Mounting height: 3.05 meters (10 feet)

Lux at center:	169 lx
3%	5.07 lx
5%	8.45 lx
10%	16.90 lx
30%	50.70 lx
50%	84.50 lx


Conditions:
Number of planes: 8
Lux distribution on a surface when lamp is mounted at 3.05 meters from the surface.

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101	101	100	98	98	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93	95	93	91	93	91	89	87
3	103	97	92	88	101	95	91	87	93	89	86	90	87	84	88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79	85	81	79	83	80	78	76
5	93	85	79	75	91	84	79	75	82	78	74	81	76	73	79	75	73	71
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	71	65	61	70	65	61	68	64	61	68	63	60	59
9	77	67	62	58	76	67	61	58	66	61	57	65	61	57	64	60	57	56
10	73	64	58	55	72	63	58	54	63	58	54	62	57	54	61	57	54	53

Luminaire Budgetary Diagram

LAMPS (number of lamps)



Conditions			
H = Room height			
Hdown	Lamp distance from ceiling		0.00m
Hwork	Work area height from floor		0.00m
Ework	Average lux on work area		100lx
p(%)	Ceiling reflectance	Wall reflectance	Floor reflectance
- - - - - - -	70	50	30
———	50	30	20


LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736

Copyright © 2023, All rights reserved.


S251XX-ETWWC-TX-XX


Photometric Testing Report


ANSI/IES TM-30-18 P: **2** / V: **-** / F: **2**




Hue Bin	R_f	Shifts (%) Chroma	Hue
1	92	-4%	0%
2	94	-3%	2%
3	93	-1%	3%
4	96	-1%	1%
5	95	-2%	1%
6	97	1%	0%
7	94	-3%	0%
8	98	-1%	1%
9	94	-1%	4%
10	90	0%	6%
11	90	2%	6%
12	91	6%	-1%
13	93	2%	-5%
14	89	3%	-8%
15	90	-1%	-6%
16	87	-2%	-10%









Red: 36.3%, Power=12.1mW

Blue: 9.8%, Power=8.1mW


Green: 25%, Power=15.3mW

UVA: 0%, Power=0.0mW

Dominant Wavelength:583nm

1st Peak Wavelength: 619nm

2nd Peak Wavelength:454nm



Copyright © 2023, All rights reserved.

Glare Evaluation According to UGR

Corrected, comprehensive UGR table according to 117-1995, S/H ratio=0.25

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size H = mouting height above eye level X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22.8	23.5	22.9	23.7	23.9	22.8	23.5	22.9	23.7	23.9
	3H	22.6	23.4	23.0	23.6	23.8	22.6	23.4	23.0	23.6	23.8
	4H	22.5	23.3	22.9	23.5	23.7	22.5	23.3	22.9	23.5	23.7
	6H	22.5	23.1	22.8	23.4	23.8	22.5	23.1	22.8	23.4	23.8
	8H	22.5	23.1	22.8	23.4	23.8	22.5	23.1	22.8	23.4	23.8
	12H	22.4	23.0	22.8	23.4	23.8	22.4	23.0	22.8	23.4	23.8
4H	2H	22.6	23.3	22.9	23.5	23.7	22.6	23.3	22.9	23.5	23.7
	3H	22.5	23.1	22.9	23.4	23.9	22.5	23.1	22.9	23.4	23.9
	4H	22.4	22.9	22.8	23.3	23.8	22.4	22.9	22.8	23.3	23.8
	6H	22.3	22.9	22.8	23.2	23.6	22.3	22.9	22.8	23.2	23.6
	8H	22.3	22.8	22.8	23.1	23.5	22.3	22.8	22.8	23.1	23.5
	12H	22.2	22.6	22.7	23.0	23.5	22.2	22.6	22.7	23.0	23.5
8H	4H	22.3	22.8	22.8	23.1	23.5	22.3	22.8	22.8	23.1	23.5
	6H	22.2	22.5	22.7	23.0	23.5	22.2	22.5	22.7	23.0	23.5
	8H	22.2	22.5	22.7	23.0	23.6	22.2	22.5	22.7	23.0	23.6
	12H	22.1	22.4	22.7	22.9	23.5	22.1	22.4	22.7	22.9	23.5
12H	4H	22.2	22.6	22.7	23.0	23.5	22.2	22.6	22.7	23.0	23.5
	6H	22.2	22.5	22.7	23.0	23.6	22.2	22.5	22.7	23.0	23.6
	8H	22.1	22.4	22.7	22.9	23.5	22.1	22.4	22.7	22.9	23.5

Variation of the observer position for the luminaire distance S		
S = 1.0H	4.9 / -6.2	4.9 / -6.2
S = 1.5H	7.5 / -7.4	7.5 / -7.4
S = 2.0H	9.5 / -10.7	9.5 / -10.7

Corrected glare indices referring to 1259 lm total luminous flux