LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2023, All rights reserved.

S254XX-MDWMC-TX-XX


Photometric Testing Report

Light efficiency:
59 Lumen/Watt

Color temperature:
3117 K


Light quality:
CRI:93.2, R_g:101.9, R_f:91.3
R9: 72.8 / P: 2 / V: - / F: 2

Output:	**1091 lm**
Peak:	2698 cd
Power:	18.4 W
Voltage:	120 V
Current:	0.156 A
PF:	0.99
THD:	11.99 %



Angular Distribution

0° and 90° plane



Product name:
S254XX-MDWMC-TX-XX

Test Date:
8/26/2026


Beam Angle (50% of the brightness of the centre):
38.7°

Field Angle (10% of the brightness of the centre):
56.4°

Cut Off Angle (2.5% of the brightness of the centre):
65.1°

Beam Details

*measured at centre of beam



LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2023, All rights reserved.


S254XX-MDWMC-TX-XX

Photometric Testing Report

Zonal Lumen Summary

Zone	Lumen	%Luminaire
0-30	1040	95.33%
0-40	1068	97.89%
0-60	1085	99.45%
60-90	4.03	0.37%
70-100	0.792	0.07%
90-120	0.164	0.02%
0-90	1089	99.82%
90-180	1.58	0.14%
0-180	1091	100.00%

ISO Lux Diagram



Mounting height: 3.05 meters (10 feet)

Lux at center:	290 lx
3%	8.70 lx
5%	14.50 lx
10%	29.00 lx
30%	87.00 lx
50%	145.00 lx


Conditions:
Number of planes: 8
Lux distribution on a surface when lamp is mounted at 3.05 meters from the surface.

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	112	110	108	112	110	108	107	106	105	103	102	101	100	99	98	97	96
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	94	93	92
3	106	101	97	94	104	100	96	93	97	94	92	95	93	91	93	91	89	88
4	103	97	92	89	101	96	92	88	94	90	87	92	89	86	90	87	85	84
5	99	92	88	85	98	92	87	84	90	86	83	88	85	83	87	84	82	81
6	96	89	84	81	94	88	84	80	87	83	80	85	82	79	84	81	79	78
7	92	85	81	77	91	85	80	77	83	80	77	82	79	76	81	78	76	75
8	89	82	77	74	88	82	77	74	81	77	74	80	76	74	79	76	73	72
9	86	79	74	71	86	79	74	71	78	74	71	77	73	71	76	73	71	70
10	84	76	72	69	83	76	72	69	75	71	69	75	71	68	74	71	68	67

***LAMPS** (number of lamps)*

Luminaire Budgetary Diagram




Conditions			
H = Room height			
Hdown	Lamp distance from ceiling		0.00m
Hwork	Work area height from floor		0.00m
Ework	Average lux on work area		100lx
p(%)	Ceiling reflectance	Wall reflectance	Floor reflectance
- - - - - - -	70	50	30
———	50	30	20

LITELINE CORPORATION | LITELINE.COM
T 416.996.1856 | 1.866.730.7704
F 905.709.5255 | 1.888.738.9736
Copyright © 2023, All rights reserved.


S254XX-MDWMC-TX-XX


Photometric Testing Report


ANSI/IES TM-30-18 P: **2** / V: **-** / F: **2**




Hue Bin	R_f	Shifts (%) Chroma	Hue
1	93	-3%	-1%
2	94	-3%	2%
3	89	-1%	6%
4	92	1%	5%
5	92	2%	4%
6	93	5%	0%
7	94	1%	-3%
8	95	0%	-3%
9	95	-3%	1%
10	88	-3%	6%
11	85	0%	10%
12	89	5%	5%
13	93	4%	0%
14	90	7%	-4%
15	91	2%	-5%
16	88	1%	-10%









Red: 39.2%, Power=12.3mW

Blue: 8.2%, Power=5.7mW


Green: 24.3%, Power=14.0mW

UVA: 0%, Power=0.0mW

Dominant Wavelength:584nm

1st Peak Wavelength: 626nm

2nd Peak Wavelength:452nm



Copyright © 2023, All rights reserved.

Glare Evaluation According to UGR

Corrected, comprehensive UGR table according to 117-1995, S/H ratio=0.25

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size H = mouting height above eye level X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	12.7	13.1	12.7	13.3	13.5	12.7	13.1	12.7	13.3	13.5
	3H	12.5	13.2	12.9	13.3	13.5	12.5	13.2	12.9	13.3	13.5
	4H	12.5	13.1	12.9	13.3	13.5	12.5	13.1	12.9	13.3	13.5
	6H	12.5	13.0	12.8	13.3	13.6	12.5	13.0	12.8	13.3	13.6
	8H	12.4	12.9	12.8	13.2	13.6	12.4	12.9	12.8	13.2	13.6
	12H	12.4	12.9	12.7	13.2	13.6	12.4	12.9	12.7	13.2	13.6
4H	2H	12.5	13.1	12.9	13.3	13.5	12.5	13.1	12.9	13.3	13.5
	3H	12.6	13.0	12.9	13.4	13.8	12.6	13.0	12.9	13.4	13.8
	4H	12.5	12.9	12.9	13.3	13.8	12.5	12.9	12.9	13.3	13.8
	6H	12.4	12.9	12.9	13.2	13.6	12.4	12.9	12.9	13.2	13.6
	8H	12.4	12.8	12.9	13.1	13.5	12.4	12.8	12.9	13.1	13.5
	12H	12.3	12.6	12.8	13.0	13.5	12.3	12.6	12.8	13.0	13.5
8H	4H	12.4	12.8	12.9	13.1	13.5	12.4	12.8	12.9	13.1	13.5
	6H	12.3	12.6	12.8	13.1	13.6	12.3	12.6	12.8	13.1	13.6
	8H	12.3	12.5	12.8	13.1	13.7	12.3	12.5	12.8	13.1	13.7
	12H	12.3	12.4	12.8	12.9	13.5	12.3	12.4	12.8	12.9	13.5
12H	4H	12.3	12.6	12.8	13.0	13.5	12.3	12.6	12.8	13.0	13.5
	6H	12.3	12.5	12.8	13.1	13.7	12.3	12.5	12.8	13.1	13.7
	8H	12.3	12.4	12.8	12.9	13.5	12.3	12.4	12.8	12.9	13.5

Variation of the observer position for the luminaire distance S		
S = 1.0H	5.2 / -3.3	5.2 / -3.3
S = 1.5H	7.8 / -4.6	7.8 / -4.6
S = 2.0H	9.7 / -7.1	9.7 / -7.1

Corrected glare indices referring to 1091 lm total luminous flux